



FINSA

Financiera Maderera, S.A. -FINSA-
Carretera A Coruña-Tui, km. 57
15884 SANTIAGO DE COMPOSTELA
SPAIN

DECLARATION OF PERFORMANCE

DoP 00006

FIBRANOR FIBRAPAN IBERPAN

Manufactured at:

FINSA PADRÓN Paraíso s/n 15900 Padrón. A Coruña. Spain	FINSA OREMBER Pol. Ind. San Cibrao das Viñas 32911 Ourense. Spain	FINSA FIBRANOR Pol. Ind. de Rábade 27370 Rábade. Lugo. Spain	LUSO FINSA - NELAS Est. Nac. 234, km. 92.7 3524-952 Nelas. Portugal
-----------------------------------------------------------------	----------------------------------------------------------------------------	-----------------------------------------------------------------------	------------------------------------------------------------------------------

Product type	Intended use	AVCP*
MDF	Internal use as non structural components in dry conditions	4
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011		

Declared performance:

Essential characteristics	Performance										Harmonised technical specification
	Thickness (mm)										
	units	1.8 to 2.5	>2.5 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	>30 to 45	>45	
Bending strength EN 310	N/mm ²	23	23	23	23	22	20	18	17	15	EN 13986:2004
Modulus of elasticity EN 310	N/mm ²	-	-	2700	2700	2500	2200	2100	1900	1700	
Internal bond EN 319	N/mm ²	0.65	0.65	0.65	0.65	0.60	0.55	0.55	0.50	0.50	
Swelling in thickness 24 hours EN 319	%	45	35	30	17	15	12	10	8	6	
Release of formaldehyde Emission EN 717-1	Class mg/m ³	E1 <0.124	E1 <0.124	E1 <0.124	E1 <0.124	E1 <0.124	E1 <0.124	E1 <0.124	E1 <0.124	E1 <0.124	
Reaction to fire EN 13501-1:2007	Class Class	NPD NPD	NPD NPD	NPD NPD	NPD NPD	D-s2,d0* Dfl,s1	D-s2,d0** Dfl,s1	D-s2,d0 Dfl,s1	D-s2,d0 Dfl,s1	D-s2,d0 Dfl,s1	
Water vapour permeability Wet cup / Dry cup Table 9 EN 13986:2004	μ	22/33	21/31	20/30	18/28	17/27	16/25	15/24	15/24	14/23	
Airborne sound insulation (surface mass) (R) 5.10 EN 13986:2004	db	NPD	NPD	NPD	22/24	24/26	26/28	29/30	30/33	33/34	
Sound absorption Frequency range 250Hz to 500Hz Table 10 EN 13986:2004	α	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	
Sound absorption Frequency range 1000Hz to 2000Hz Table 10 EN 13986:2004	α	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Thermal conductivity (λ) Table 11 EN 13986:2004	W/(m.K)	0.16	0.15	0.15	0.13	0.13	0.12	0.12	0.12	0.11	
Biological durability	Use classes	1	1	1	1	1	1	1	1	1	
Content of pentachlorophenol (PCP)	ppm	<5	<5	<5	<5	<5	<5	<5	<5	<5	



FINSA

Financiera Maderera, S.A. -FINSA-
Carretera A Coruña-Tui, km. 57
15884 SANTIAGO DE COMPOSTELA
SPAIN

(*) Mounted without an air gap behind the FIBRANOR FIBRAPAN IBERPAN. Mounted with a closed air gap not more than 22 mm behind the FIBRANOR FIBRAPAN IBERPAN classification D-s2,d2. Classification E for any other more restrictive condition. Commission Decision 2007/348/EC

(**) Mounted without an air gap behind the FIBRANOR FIBRAPAN IBERPAN, or with a closed air gap behind the FIBRANOR FIBRAPAN IBERPAN for thicknesses equal or greater than 15mm or with an open air gap behind the FIBRANOR FIBRAPAN IBERPAN for thicknesses equal or greater than 18 mm. Mounted with a closed air gap not more than 22 mm behind the FIBRANOR FIBRAPAN IBERPAN classification D-s2,d2 in thicknesses between 10 and 18 mm. . Commission Decision 2007/348/EC.

The performance of the product FIBRANOR FIBRAPAN IBERPAN is in conformity with the above declared performance.
This declaration of performance is issued under the sole responsibility of Financiera Maderera, S.A. –FINSA- .

Javier Portela
FINSA IDi + Quality Director
Santiago de Compostela, January 2nd 2014